

RAMPO HDMI EXTENDERS RMP-40G2



SPECIFICATIONS

Audio and Video

	Transmitter	Receiver
Inputs	1x HDMI 19-pin type A	1x UTP 8-pin RJ-45 female
Outputs	1x UTP 8-pin RJ-45 female	1x HDMI 19-pin type A
Audio Formats	2ch PCM Up to 7.1 DTS-HD Master Audio and Dolby TrueHD	
Video Resolutions (Max)	Video Resolutions 1920x1200p @60Hz 16bit	Cat6 120m
Supported Standards	DCI	
Maximum Pixel Clock	297mHz	

TRANSMISSION DISTANCE REACHES UP TO 100 METERS UNDER THE VIDEO FORMAT OF 1080P AND 4K UP TO 70 METERS

Communication and Control

HDMI	HDCP EDID DVI/D supported with adapter (not included)
UTP	EDID Bidirectional IR
IR	Bidirectional over UTP

Power

Power Supply	Input: 100~240V AC 50/60Hz Output: 12V DC 0.5A
Max Power Consumption	5W

Environmental

Operating Temperature	32°F ~ 113°F (0°C ~ 45°C) 10% ~ 90%, non-condensing
Storage Temperature	-4°F to ~ 158°F (-20°C ~ +70°C) 10% ~ 90%, non-condensing
Maximum BTU	17.06 BTU/hr